



G Drive - R550 series



Class
Leading
NVH



Compact
Design



Available In
1500 & 1800 RPM



Low
Maintenance
Cost



Low Fuel
Consumption



Wide Power
Range

Game Changing Features:

- Electronic governor as standard feature
- Best in class integral actuator with position monitoring
- Electrical fuel transfer pump as standard feature
- Engine wiring harness supplied as standard feature
- ECU compatible for CAN communication
- Generating set controller offered as optional
- Communication with CAN enabled controllers is feasible
- Multi-tier stackable with different combinations

KIRLOSKAR MAKE, LIQUID COOLED, 4 STROKE, DIESEL ENGINE				1500 RPM			
Make				Kirloskar	Kirloskar	Kirloskar	Kirloskar
Model				2R550NA	3R550NA	3R550TC	3R550TA
Engine output as per ISO3046	PRP	hp/kWm		14.0 / 10.3	20.9 / 15.4	25.5 / 18.7	36 / 26.5
Cyls & configuration				2-Inline	3-Inline	3-Inline	3-Inline
Bore x Stroke		mm		86 x 94	86 x 94	86 x 94	86 x 94
Compression ratio				19.7 : 1	19.7 : 1	19.7 : 1	19.7 : 1
Displacement		L		1.1	1.65	1.65	1.65
Aspiration				Natural	Natural	Turbocharged	Turbocharged Aftercooled
Starting System DC)				12V	12V	12V	12V
Governor				Electronic	Electronic	Electronic	Electronic
Governing class as per ISO8528-5				G2	G2	G2	G2
Lub oil sump capacity- refill		L		3.8	6.5	6.5	6.5
Coolant capacity		L		TBA	TBA	TBA	TBA
Battery rating		AH		65	65	65	65

KIRLOSKAR MAKE, LIQUID COOLED, 4 STROKE, DIESEL ENGINE				1800 RPM			
Make				Kirloskar	Kirloskar	Kirloskar	Kirloskar
Model				2R550NA	3R550NA	3R550TC	3R550TA
Engine output as per ISO3046	PRP	hp/kWm		16.1 / 11.8	24 / 17.6	31 / 22.8	42 / 30.9
Cyls & configuration				2-Inline	3-Inline	3-Inline	3-Inline
Bore x Stroke		mm		86 x 94	86 x 94	86 x 94	86 x 94
Compression ratio				19.7 : 1	19.7 : 1	19.7 : 1	19.7 : 1
Displacement		L		1.1	1.65	1.65	1.65
Aspiration				Natural	Natural	Turbocharged	Turbocharged Aftercooled
Starting System DC)				12V	12V	12V	12V
Governor				Electronic	Electronic	Electronic	Electronic
Governing class as per ISO8528-5				G2	G2	G2	G2
Lub oil sump capacity- refill		L		3.8	6.5	6.5	6.5
Coolant capacity		L		TBA	TBA	TBA	TBA
Battery rating		AH		65	65	65	65

Global Presence

KIRLOSKAR DMCC

JBC - 5, Cluster W, Jumeirah Lake Towers, P.O. Box 37745 Dubai U.A.E
 Tel.: +971 4 443 8591
 Fax : +971 4 441 4532
 Email : enquiry@kirloskarib.com
 Email : enquiry@kirloskar.ae
 Website : www.kirloskarib.com

KIRLOSKAR TRADING SA (PTY) LTD.

Unit B1, The Stables Business Park, Cnr of Third Avenue & Second Road, Limbro Park, Modderfontein, Johannesburg.
 Tel. : +27 11 553 6900 / 6903
 Email : prem.shankar@kirloskar.com

KIRLOSKAR KENYA LTD.

P.O Box 60061, Off Dunga Road, Nairobi, Kenya,
 Tel. : +254 20 653 6632
 Fax : +254 20 653 3390
 Email : raj.patil@kirloskar.com

KIRLOSKAR AMERICAS CORPORATION

33300 Egypt Lane, Suite C300 Mangolia, TX 77354
 Tel. : +1 346 248 5777
 Cell Ph : +1 832 675 1595
 Fax : +1 830 423 8060
 Email : info@koelamerica.com



KIRLOSKAR OIL ENGINES LIMITED

A Kirloskar Group Company

Regd. Office : 13, Laxmanrao Kirloskar Road, Khadki, Pune, Maharashtra 411 003 INDIA
 Tel.: +91(20) 2581 0341 Fax: +91(20) 2581 3208, 2581 0209
 Helpline: +91 8806 33 44 33
 Email: koel.helpdesk@kirloskar.com Website: kirloskaroilengines.com

- Technical details mentioned above may vary as per site condition / situation. As continuous improvements are contemplated the description and illustrations are not binding.
- This catalogue is copyrighted and may not be reproduced in any form, not even parts of it, without previous written permission by copyright owners, Kirloskar Oil Engines Ltd.
- Mark 'Kirloskar' used in any form as prefix or suffix is owned by Kirloskar Proprietary Limited and Kirloskar Oil Engines Limited is permitted user.